

Expert finishes for wood and metal

Rustins Ltd, Waterloo Road, London NW2 7TX. Tel: +44 (0)20 8450 4666 www.rustins.co.uk

February 2018

PRODUCT DATA SHEET

Product	Decking Oil
Туре	A blend of oils, resins and driers, with added UV absorbers and biocide to protect the oil from mould.
Intended Use	Timber decks and can also be used for all types of exterior wood, and wooden garden furniture.
Special Features	Brings out the natural beauty of wood. Easy to apply and maintain.
Preparation	The bare wood must be clean, smooth, dry, and free of dust and contaminants. Rustins Decking Cleaner can be used to clean the surface. Do not apply to damp timber as this will prevent the oil from penetrating the timber and adhering causing it to flake off.
Application	Apply liberally with a clean brush allowing 4-8 hours between coats. Do not apply if rain is expected.
Coats	3 coats.
Drying Time	4-8 hours, depending on temperature & Humidity.
Re-coating Time	4-8 hours, depending on temperature & Humidity.
Application Temp.	Ideally 15-25°C but do not apply below 5°C.
Coverage	About 12 sq.m per litre per 1 coat.
Maintenance	Periodic re-oiling is required. When applying to previously oiled wood the surface should be cleaned thoroughly and be free from contaminants.
Compatibility	May be used over existing oil based finishes but test for compatibility with a small test area first.
Settlement	SHAKE WELL BEFORE USE.
Shelf-life/Storage	Many years if stored in original, tightly closed container in cool, dry conditions.
Hazards	Flammable. Avoid contact with eyes and skin. Use in a well ventilated area. Keep out of reach of children. Keep away from sources of ignition – no smoking. Keep container tightly closed. A full Safety Data Sheet is available upon request or on www.rustins.co.uk .
Clean-Up	Clean brushes with white spirit or Rustin's Brush Cleaner whilst still wet. Hard brushes can be cleaned with Rustin's Brush Restorer .
Sizes	2.5 L 5L.