

**PRODUCT DATA SHEET**

<b>Product</b>	<b>Quick Dry Outdoor Woodstain</b>
<b>Type</b>	Coloured water-based acrylic varnish, available in Gloss or Satin. Gives long lasting protection to all external wood, allowing the natural grain to show through.
<b>Intended Use</b>	Exterior joinery both hard & softwood, doors, windows, garden furniture, conservatories. May also be used as a sealer for concrete. NOTE: use Rustins Quick Dry Decking Oil on timber decking.
<b>Special Features</b>	Low odour, resists cracking, peeling, blistering. Wash brushes in water. Available in Light, Medium or Dark Oak, Mahogany, Teak, Walnut and Ebony
<b>Preparation</b>	Surfaces must be clean, dry and free of wax, grease and contaminants, smooth and sound. Fill large cracks, open joints and damaged areas with a high quality flexible filler. Wash oily woods, knots or resinous areas with white spirit. Remove mould, lichens, algae & moss with brush, scraper & domestic bleach, then rinse thoroughly and allow to dry. <b>Rustins Wood Dye</b> may be applied to bare wood prior to varnishing.
<b>Application</b>	Using a synthetic brush, apply liberally with a full brush finishing with the grain. The first coat may be diluted with water on hot days (up to 15%). Do not apply to hot surfaces or in strong sunlight if possible or if rain is likely.
<b>Coats</b>	Apply 3 coats and lightly sand after 1st coat if there is raising of the grain.
<b>Drying Time</b>	Touch dry 30 minutes. (On hot days may be touch dry within 10 minutes).
<b>Re-coating Time</b>	4 hours minimum, depending on temperature & humidity.
<b>Application Temp.</b>	Ideally 15-25°C. Do not apply below 10°C, or in high humidity or if rain expected.
<b>Coverage</b>	12-15 sq. metres per litre per coat, depending on absorbency of surface.
<b>Maintenance</b>	Re-coat every 2 to 3 years. Clean with a mild detergent solution and lightly sand to provide key.
<b>Compatibility</b>	May be applied over old existing coating if these are in good condition and rubbed down to provide a key. Coatings not in good condition should be removed with <b>Rustins Strypit Paint and Varnish Stripper</b> . If applying over wood preservatives test on a small area to ensure the varnish dries and adheres well.
<b>Settlement</b>	<b>STIR WELL BEFORE USE.</b> May dry glossy if not adequately stirred.
<b>Shelf-life/Storage</b>	Many years if stored in original, tightly closed container in normal conditions. <b>PROTECT FROM FROST.</b>
<b>Hazards</b>	Non-flammable. Avoid contact with eyes, skin and clothes. A full Safety Data Sheet is available upon request or on <a href="http://www.rustins.co.uk">www.rustins.co.uk</a>
<b>Clean-Up</b>	With water whilst still wet. If dried-on, clean equipment & brushes with <b>Rustins Brush Restorer</b> .
<b>Sizes</b>	250ml 500ml 1 L 2.5 L