

March 2020

PRODUCT DATA SHEET

Product	Quick Dry Textured Decking Oil
Type	A blend of water-resistant oils and polymers with added UV absorbers and biocide to protect the oil from mould.
Intended Use	For softwood, hardwood and composite decking. Can also be used for all types of exterior wood, and wooden garden furniture.
Special Features	Suitable for hardwood, softwood and composite decking. Water-based. Low odour. Low toxicity. Hard-wearing. Increases water-repellency of wood. Gives a satin finish. Nourishes and protects wood. Brings out the natural beauty of wood. Easy to apply and maintain. Can be applied to still damp timber. Cured surface finish rated as 'low slip potential' according to BS 7976, Part 2, 2002; Assessment of slip resistance in both dry and wet conditions.
Preparation	The bare wood must be clean, smooth, dry, and free of dust, dirt, wax, algae, mould and other contaminants. Where the deck is weather-stained, discoloured or of poor appearance Rustins Decking Cleaner or Rustins Composite Decking Cleaner can be used to clean and revive the wooden surface prior to application of Rustins Quick Dry Decking Oil .
Application	Stir well before use. Apply liberally with a clean brush, (use largest practical size of brush, ideally synthetic bristle type designed for applying water-base varnishes), allowing a minimum of 3 hours between coats. Try to keep a wet edge as overlapping a dry film will produce a darker patch, as will drips and runs.
Coats	Minimum of 2 coats. Extra coats may be required for softwood or weathered decking. Note the final colour will depend on the original colour of the wood and the number of coats applied.
Drying Time	Touch dry in 30 mins. Dries in 3 hours depending on temperature & humidity.
Re-coating Time	Minimum of 3 hours, depending on temperature & humidity.
Application Temp.	Ideally 15-25°C, Do not apply below 10°C, in high humidity/damp conditions or if rain imminent.
Coverage	About 14 sq. m per litre per 1 coat.
Maintenance	Periodic re-oiling is required. When applying to previously oiled wood the surface should be cleaned thoroughly and be free from contaminants.
Compatibility	May be used over existing oil based finishes but test for compatibility on a small test area first. If applying over wood previously treated with a wood preserver, also test a small area first to ensure the decking oil dries and adheres well.
Settlement	SHAKE WELL BEFORE USE.
Shelf-life/Storage	Many years if stored in original, tightly closed container in cool, dry conditions.
Hazards	Avoid contact with eyes, skin and clothing. If medical advice is needed, have product container or label at hand. Do not eat, drink or smoke while using this product. Wear personal protective equipment (PPE) as required. Keep out of reach of children. Keep container tightly closed. A full Safety Data Sheet is available upon request or on www.rustins.co.uk .
Clean-Up	Remove surplus material and return to container. Clean brushes with water whilst still wet. Hard brushes can be cleaned with Rustins Brush Restorer .
Sizes	2.5 Lits.